

## ◆ LEAD FORMING TYPE

Type	Code	ΦD	F	L1	Dimensions (Unit: mm)																									
					L (Part number for lead length and pitch for taping)																									
					Z	2	B	E	G	M	Q	S	T	F	H	3	C	D	4	5	6	7	I	8	J	9	K	A	L	
					2.0	2.5	2.8	3.1	3.3	3.5	3.6	1.0	3.8	14.8	12	3.5	3.8	4.0	4.5	5.0	6.3	7.0	7.5	8.0	8.5	9.0	9.5	10	10.5	
					+0.3 / -0.2							±0.3							±0.5											
Cut	C	4	1.5	----																										Fig 1
		5	2.0	----																										
		6.3	2.5	----																										
		8	3.5	----																										
		10	5.0	----																										
		12.5	5.0	----																										
		16	7.5	----																										
		18	7.5	----																										
		20	10	----																										
		22	10	----																										
Kink & Cut	B	4	5.0	1.1																										Fig 2
		5	5.0	1.1																										
		6.3	5.0	1.1																										
		8	5.0	1.3																										
		10	5.0	1.3																										
		12.5	5.0	1.3																										
		16	7.5	1.3																										
		18	7.5	1.3																										
Form & Cut	D	8	2.5	----																										Fig 3
		4	5.0	----																										
	F	5	5.0	----																										Fig 4
		6.3	5.0	----																										
		8	5.0	----																										

# PACKING



## ◆ TAPING ( Applicable standard JIS C 0806-3)

### Conductive Polymer Aluminum Solid Capacitors / Conductive Polymer Hybrid Aluminum Electrolytic Capacitors

Fig 10	Symbol	Tolerance	Φ 5		Φ 6.3		Φ 8	
			PS	P5	PS	P5	PS	P5
	Φd	±0.05	0.45		0.45/0.6		0.6	
	P	±0.1	12.7		12.7		12.7	
	P0	±0.2	12.7		12.7		12.7	
	P1	±0.5	3.85		3.85		3.85	
	P2	±1.0	6.35		6.35		6.35	
	F	0.8 -0.2	5		5		5	
	H	±0.5	17.5	18.5	17.5	18.5	17.5	18.5
	H0	±0.5	16		16		16	
	W	±0.5	18		18		18	
	W0	Minimum	12.5		12.5		12.5	
	D0	±0.2	4		4		4	
	t	±0.2	0.7		0.7		0.7	

Fig 11	Symbol	Tolerance	Φ 6.3	Φ 8			Φ 10		
			P2	P3	H3	P7	P5	H5	J5
	Φd	±0.05	0.45/0.6		0.6			0.6	
	P	±0.1	12.7		12.7			12.7	
	P0	±0.2	12.7		12.7			12.7	
	P1	±0.5	5.1		4.6			3.85	
	P2	±1.0	6.35		6.35			6.35	
	F	+0.8 -0.2	2.5		3.5			5	
	H	±0.5	18.5	18.5	20	17.5	18.5	20	21
	H0	±0.5	-		-			-	
	W	±0.5	18		18			18	
	W0	Minimum	12.5		12.5			12.5	
	D0	±0.2	4		4			4	
	t	±0.2	0.7		0.7			0.7	

Fig 12	Symbol	Tolerance	Φ 5
			PZ
	Φd	±0.05	0.45
	P	±0.1	12.7
	P0	±0.2	12.7
	P1	±0.5	5.35
	P2	±1.0	6.35
	F	+0.8 -0.2	2.0
	H	±0.5	18.5
	H0	±0.5	-
	W	±0.5	18
	W0	Minimum	12.5
	D0	±0.2	4
	t	±0.2	0.7

#### Packing quantity

ΦD	Size		Inner box	Carton box
	L	Q'ty (Pcs)	Q'ty (Pcs)	Q'ty (Pcs)
5	8~12	2,500	12,500	
5.5	8~12	2,200	11,000	
6.3	5~12	2,000	10,000	
	16	2,000		
8	6~12	1,000	5,000	
	16~22	1,200		
10	7~12	800	4,000	
	16~22	800		