



◆ MARKING AND DATE CODE

Trade Mark "CS"	Chinsan Solid Capacitor, Show on Dimension $\geq 8\phi$																																																
Code (Date Code) <table style="margin-left: 20px;"> <tr> <td>(1)</td> <td>(2)</td> <td>(3)</td> </tr> <tr> <td style="border: 1px solid black; padding: 2px;">1</td> <td style="border: 1px solid black; padding: 2px;">5</td> <td style="border: 1px solid black; padding: 2px;">8</td> </tr> </table>	(1)	(2)	(3)	1	5	8	(1)DAY																																										
	(1)	(2)	(3)																																														
	1	5	8																																														
	Code		1	2	3																																												
Day		1st~10th	11~20th	21st~31st																																													
(2)Month																																																	
Code		1	2	3	4	5	6																																										
Month		Jan	Feb	Mar	Apr	May	Jun																																										
Code		7	8	9	X	Y	Z																																										
Month		July	Aug	Sep	Oct	Nov	Dec																																										
(3)Year																																																	
Code		6	7	8	9	0	1																																										
Year		2016	2017	2018	2019	2020	2021																																										
Series (Print Code)	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Series</th> <th>UPS</th> <th>UPR</th> <th>UL</th> <th>UPE</th> <th>RP</th> <th>RH</th> <th>GP</th> <th>GV</th> <th>GS</th> <th>SG</th> <th>SP</th> <th>SU</th> <th>SE</th> </tr> </thead> <tbody> <tr> <td>$\phi 5 \sim \phi 6.3$</td> <td>--</td> <td>R</td> <td>L</td> <td>E</td> <td>--</td> <td>H</td> <td>P</td> <td>V</td> <td>--</td> <td>G</td> <td>P</td> <td>U</td> <td>E</td> </tr> <tr> <td>$\phi 8 \sim \phi 10$</td> <td>UPS</td> <td>--</td> <td>UL</td> <td>UPE</td> <td>RP</td> <td>RH</td> <td>GP</td> <td>GV</td> <td>GS</td> <td>SG</td> <td>SP</td> <td>SU</td> <td>SE</td> </tr> </tbody> </table>							Series	UPS	UPR	UL	UPE	RP	RH	GP	GV	GS	SG	SP	SU	SE	$\phi 5 \sim \phi 6.3$	--	R	L	E	--	H	P	V	--	G	P	U	E	$\phi 8 \sim \phi 10$	UPS	--	UL	UPE	RP	RH	GP	GV	GS	SG	SP	SU	SE
Series	UPS	UPR	UL	UPE	RP	RH	GP	GV	GS	SG	SP	SU	SE																																				
$\phi 5 \sim \phi 6.3$	--	R	L	E	--	H	P	V	--	G	P	U	E																																				
$\phi 8 \sim \phi 10$	UPS	--	UL	UPE	RP	RH	GP	GV	GS	SG	SP	SU	SE																																				

◆ LEAD FORMING TYPE

Type	Part Number	Dimensions (Unit: mm)															
		ϕD	F	t	L (Part number for lead length and pitch for taping)												
					3	4	U	7	D	X	R	B	E	G	2	M	T
					3.5	4.5	5.5	7	4	2.3	2.5	2.8	3.1	3.3	2.5	3.5	3.8
					± 0.5					± 0.2			± 0.3				
Cut	C	5	2	----													
		6.3	2.5	----													
		8	3.5	----													
		10	5	----													

◆ TAPING

Figure 1	Symbol	Tolerance	Φ 5		Φ 6.3		Φ 8	
			PS	P5	PS	P5	PS	P5
	Φd	±0.05	0.45		0.45/0.6		0.6	
	P	±0.1	12.7		12.7		12.7	
	P0	±0.2	12.7		12.7		12.7	
	P1	±0.5	3.85		3.85		3.85	
	P2	±1.0	6.35		6.35		6.35	
	F	+0.8	5		5		5	
		-0.2						
	H	±0.5	17.5	18.5	17.5	18.5	17.5	18.5
	H0	±0.5	16		16		16	
	W	±0.5	18		18		18	
	W0	Minimum	12.5		12.5		12.5	
	D0	±0.2	4		4		4	
	t	±0.2	0.7		0.7		0.7	

Figure 2	Symbol	Tolerance	Φ 6.3	Φ 8			Φ 10
			P2	P3	H3	P7	P5
	Φd	±0.05	0.45/0.6	0.6			0.6
	P	±0.1	12.7	12.7			12.7
	P0	±0.2	12.7	12.7			12.7
	P1	±0.5	5.6	4.6			4.6
	P2	±1.0	6.35	6.35			6.35
	F	+0.8	2.5	3.5			5
		-0.2					
	H	±0.5	18.5	18.5	20	17.5	18.5
	H0	±0.5	-	-			-
	W	±0.5	18	18			18
	W0	Minimum	12.5	12.5			12.5
	D0	±0.2	4	4			4
	t	±0.2	0.7	0.7			0.7

Figure 3	Symbol	Tolerance	Φ 5
			PZ
	Φd	±0.05	0.45
	P	±0.1	12.7
	P0	±0.2	12.7
	P1	±0.5	5.6
	P2	±1.0	6.35
	F	+0.8	2.0
		-0.2	
	H	±0.5	18.5
	H0	±0.5	-
	W	±0.5	18
	W0	Minimum	12.5
	D0	±0.2	4
	t	±0.2	0.7